

DA3000

Standalone Touch Door Access Controller

DA3000 standalone door access controller is a cost-effective solution for indoor systems, where user access verification through Card-only, Card & PIN, or PIN-only is required. This durable model can be easily programmed with up to 1,000 users for a single door. DA3000 offers a user friendly set up, simplified deployment, configuration and operation. The unit comes with optional tamper-proof solution.



DA3000 Door Access controller

Features:


- 1000 Users (Card/PIN)
- Card Format: 26 bit Wiegand
- Operation Mode: PIN/Card/Card+PIN
- Lock Release Time (00-99 sec)
- Keypad Lock
- Built in Buzzer
- Touch Panel Keypad
- Piano Gloss Finishing
- Supports Exit Reader
- Doorbell Button

No.	Specification	Parameter
1	Operating Voltage	DC12v +/- 10%
2	Operating Current	<100mA
3	Dimensions	78mm x 120mm x 22mm
4	Weight	130g
5	Ambient Temperature	-10°C to 70°C
6	Relative Humidity	20% to 80%
7	Storage	1000 users
8	Card Type (alternative)	EM(ID) card (IC card optional)
9	Card Reading Distance	1 to 15cm

DA3000

Standalone Touch Door Access Controller Wiring Diagram

METHOD 1: STANDARD INSTALLATION



METHOD 2: TAMPER-PROOF INSTALLATION

